Shell Omala S4 WE 220

Version 1.9

Revision Date 09.05.2023

Print Date 20.04.2024

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name :	Shell Omala S4 WE 220
----------------	-----------------------

Product code : 001D7857

Manufacturer/Supplier	 Shell India Markets Private Limited Commerzone, Block-2, No.2 200 Feet Radial Road Pallikaranai CHENNAI 600100 India
Telephone Telefax	: (+91) 04446945100 : (+91) 04443451516
Emergency telephone number Recommended use of the che Recommended use	: +91 22 6516 1058 emical and restrictions on use : Gear lubricant.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend of polyalkylene glycol and additives.

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Alkaryl amine	68411-46-1	Repr. 2; H361	0.1 - 0.9
Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate < 5%]	68937-41-7	Repr. 2; H361 STOT RE 2; H373 Aquatic Chronic 4; H413	0.1 - 0.5
(4- nonylphenoxy)acetic acid	3115-49-9	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400	0.01 - 0.099

_

Shell Omala S4 WE 220

Version 1.9	Revision Date 09.05.2023	Print Date 20.04.2024
	Aquatic Chronic 1; H410	

For explanation of abbreviations see section 16.

3. HAZARDS IDENTIFICATION

Based on available data this substance / mixture does not meet the classification criteria.

Label elements

Safety data sheet available on request.

Hazard pictograms Signal word	 No Hazard Symbol required No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: Not classified as a health hazard under CLP criteria. ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.
Precautionary statements	 Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases. Disposal: No precautionary phrases.

Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

FIRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

4.

Version 1.9	Revision Date 09.05.2023 Print Date 20.04.2024
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	 Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Avoid contact with skin and eyes.
protective equipment and	
emergency procedures	
Environmental precautions	: Use appropriate containment to avoid environmental

Version 1.9		Revision Date 09.05.2023	Print Date 20.04.202
		contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.	
		Local authorities should be advise cannot be contained.	d if significant spillages
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accider Prevent from spreading by making or other containment material. Reclaim liquid directly or in an abs Soak up residue with an absorben suitable material and dispose of pr	a barrier with sand, earth orbent. t such as clay, sand or othe
Additional advice	:	For guidance on selection of perso see Section 8 of this Safety Data S For guidance on disposal of spilled this Safety Data Sheet.	Sheet.
HANDLING AND STORAGE			
General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal this material. 		eet as input to a risk s to help determine
Advice on safe handling	:	Avoid prolonged or repeated conta Avoid inhaling vapour and/or mists	

, lation of care framewing	Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Product Transfer :	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.

Packaging material: Suitable material: For containers or container linings, use mild
steel or high density polyethylene.
Unsuitable material: PVC.Container Advice: Polyethylene containers should not be exposed to high
temperatures because of possible risk of distortion.

Shell Omala S4 WE 220

Version 1.9

Revision Date 09.05.2023

Print Date 20.04.2024

Specific use(s)

: Not applicable.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating,

sion 1.9	Revision Date 09.05.2023	Print Date 20.04.20
	drinking, and/or smoking. Routing protective equipment to remove of contaminated clothing and footwe Practice good housekeeping.	contaminants. Discard
Personal protective equip	ment	
Protective measures		
Personal protective equipme PPE suppliers.	ent (PPE) should meet recommended na	ational standards. Check w
Respiratory protection	 No respiratory protection is ordinations of use. In accordance with good industriations should be taken to avoid the engineering controls do not mate concentrations to a level which is health, select respiratory protective specific conditions of use and me Check with respiratory protective Where air-filtering respirators are appropriate combination of mask Select a filter suitable for the command vapours and particles [Type 4 (149°F)]. 	al hygiene practices, void breathing of material. intain airborne adequate to protect worke on equipment suitable for th eting relevant legislation. equipment suppliers. suitable, select an and filter. bination of organic gases
Hand protection Remarks	: Where hand contact with the proc	fuct may occur the use of
	gloves approved to relevant stand US: F739) made from the followir suitable chemical protection. PVC gloves Suitability and durability of usage, e.g. frequency and duratic resistance of glove material, dext from glove suppliers. Contaminat replaced. Personal hygiene is a k care. Gloves must only be worn of gloves, hands should be washed Application of a non-perfumed mo	dards (e.g. Europe: EN374 ng materials may provide C, neoprene or nitrile rubbe a glove is dependent on on of contact, chemical erity. Always seek advice ed gloves should be ey element of effective har on clean hands. After using and dried thoroughly.
	For continuous contact we recom breakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we re recognize that suitable gloves offer may not be available and in this of time maybe acceptable so long a and replacement regimes are folled a good predictor of glove resistant dependent on the exact composit Glove thickness should be typicalt depending on the glove make and	240 minutes with preference gloves can be identified. F ecommend the same but ering this level of protection case a lower breakthrough s appropriate maintenance owed. Glove thickness is n ice to a chemical as it is ion of the glove material. Ily greater than 0.35 mm
Eye protection	: If material is handled such that it protective eyewear is recommend	

Version 1.9	Revision Date 09.05.2023	Print Date 20.04.2024
Skin and body protection	 Skin protection is not ordinarily requi work clothes. It is good practice to wear chemical r 	
Thermal hazards	: Not applicable	
Environmental exposure con	trols	
General advice	 Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plan before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. 	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	colourless
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-39 °C / -38 °F Method: ISO 3016
Melting / freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
Flash point	:	278 °C / 532 °F Method: ISO 2592
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not classified as flammable but will burn.
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)

Shell Omala S4 WE 220

rsion 1.9	Revision Date 09.05.2023	Print Date 20.04.2024
Relative vapour density	: > 1estimated value(s)	
Relative density	: 1.074 (15 °C / 59 °F)	
Density	: 1,074 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: Moderate	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar p	products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 222 mm2/s (40.0 °C / 104.0 °F) Method: Unspecified	
	34.4 mm2/s (100 °C / 212 °F) Method: Unspecified	
Explosive properties	: Classification Code: Not classified	ł
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be	e a static accumulator.
Particle size	: Data not available	

10. STABILITY AND REACTIVITY	
Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition	: No decomposition if stored and applied as directed.

Shell Omala S4 WE 220

Version 1.9

Revision Date 09.05.2023

Print Date 20.04.2024

products

11. TOXICOLOGICAL INFORMATION			
Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).		
Information on likely routes of exposure	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.		
Acute toxicity			
Product:			
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.		
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.		
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

(4-nonylphenoxy)acetic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Version 1.9	Revision Date 09.05.2023	Print Date 20.04.2024

Product:

-

Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Alkaryl amine	No carcinogenicity classification.
Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate < 5%]	No carcinogenicity classification.
(4-nonylphenoxy)acetic acid	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The

Version 1.9Revision Date 09.05.2023Print Date 20.04.2024

concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION		
Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
<u>Components:</u> (4-nonylphenoxy)acetic acid	:	
M-Factor (Short-term (acute) aquatic hazard)	:	1
Persistence and degradability		
Product:		
Biodegradability	:	Remarks: Not readily biodegradable., Major constituents are

Version 1.9	Revision Date 09.05.2023	Print Date 20.04.2024
	inherently biodegradable, but contains components that may persist in the environment.	
Bioaccumulative potential		
Product:		
Bioaccumulation	Remarks: Contains components with bioaccumulate.	the potential to
Partition coefficient: n-	log Pow: > 6Remarks: (based on infor products)	mation on similar
Mobility in soil		
Product:		
Mobility	Remarks: Liquid under most environmenters soil, it will adsorb to soil particle mobile.	
Other adverse effects		
no data available Product:		
Additional ecological : information	Does not have ozone depletion potent ozone creation potential or global war is a mixture of non-volatile component released to air in any significant quant conditions of use. Poorly soluble mixture., Causes physi organisms.	ming potential., Product ts, which will not be tities under normal

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides

Version 1.9	Revision Date 09.05.2023	Print Date 20.04.2024
	technical aspects at controlling pollution	ns from ships.
Contaminated packaging	Dispose in accordance with prevailing r to a recognized collector or contractor. the collector or contractor should be es Disposal should be in accordance with national, and local laws and regulations	The competence of tablished beforehand. applicable regional,
Local legislation Remarks	 Disposal should be in accordance with national, and local laws and regulations 	

14. TRANSPORT INFORMATION

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

Other international regulations

The components of this product are reported in the following inventories:TSCA: Notified with Restrictions.

Full text of H-Statements

Version 1.9

16. OTHER INFORMATION

I dil text of IT oldterife	
H302 H314 H317 H361 H373 H400 H410 H413	Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.
Full text of other abbreviations	
Acute Tox. Aquatic Acute Aquatic Chronic Repr. Skin Corr. Skin Sens. STOT RE	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Reproductive toxicity Skin corrosion Skin sensitisation Specific target organ toxicity - repeated exposure
Abbreviations and Acro	nyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
SDS Regulation	: Regulation 1907/2006/EC
Further information	
Training advice	: Provide adequate information, instruction and training for operators.
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data use compile the Safety Data Sheet	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.